FU7350W

Opening detector, 2m, 2–core, white

The opening detector is a magnetic contact for protecting doors and windows. Unauthorised opening is detected and reported to the alarm centre.

The opening detector consists of a magnetic contact (reed) and a magnet. These are fitted parallel, in front of or at right angles to each other at a maximum distance of 13 mm apart. The electric circuit of this NC opening detector is closed in normal state (NC). If the distance between the reed and the magnet increases, the circuit is broken and an alarm reported.

The optimum installation location is the middle of the door or window frame. It can also be fitted to the bottom of the window frame if a particular window with a magnetic contact is to be tilted open. The detector is suitable for both flush and surface–mounted installation.
The opening detector is available in white and brown.

Product highlights:

- For reliable perimeter protection
- For protecting doors and windows
- Suitable for flush and surface mounting

© 2012 ABUS Security–Center GmbH & Co. KG, Errors and omissions excepted.

FU7350W

Opening detector, 2m, 2–core, white

Technical Data	
Cable length	2 metres
Cores	2–core
Switch power	0.2A / 5 Watt
Stray field protection	No
Installation	Integration / surface mounting
Dimensions in mm	11x12x48
Switch contact	NC

© 2012 ABUS Security–Center GmbH & Co. KG, Errors and omissions excepted.